



**DECLARATION OF PERFORMANCE (NO: 04.PB 1504-03.004, 2163-CPR-0561-1)
EU Construction Products Directive Annex 3 (305/2011/EU)**

1. Unique identification code of the product-type: **MYFIX TH-500 Repair mortar fine/thick**
2. Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation): Principle 3: Renovation of concrete
Method 3.1: Mortar implementation by hand
Method 3.2: Re-casting concrete
(R2)
3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: EN 1504-3:2008
4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation): **YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.**
İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad.
No:22 Dilovası / KOCAELİ / TURKEY
5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation): Not relevant
6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation): System 2+
7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: **UNIVERSAL CERTIFICATION and identification number 2163** are used for the evaluation and verification of the performance of the system under **the control of the factory production** under **System 2+** and **the continuous monitoring, measurement and evaluation of the initial inspection and the factory production control of the production facility, the performance consistency certificate, factory production conformity certificate/test.**
8. European Technical Assessment References: Not relevant
9. Declared performance:

Essential characteristics	Performance	Harmonised Technical Specifications
Compressive strength	Class R2; ≥ 15 MPa	EN 12190
Chloride ion content	NPD	EN 1015-17
Bond strength formed by adhesion	≥ 0.8 MPa	EN 1542
Restrained shrinkage / expansion	≥ 0.8 MPa	EN 12617-4
Resistance to carbonation	NPD	EN 13295
Elasticity module	NPD	EN 13412
Capillary water absorption	A1 (Organic matter <1%)	EN 13501-1

*Our products do not contain hazardous substances for health and the environment.

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entire liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 23.11.2021